

Halar<sup>®</sup>



**SOLVAY**

asking more from chemistry<sup>®</sup>



**Halar<sup>®</sup> ECTFE**  
Innovative Waterborne Coating System

**SPECIALTY  
POLYMERS**



# Halar® ECTFE

## Innovative Waterborne Coating System

### The Best Choice for Over 40 Years

Halar® ECTFE powder coatings have been used since 1975 as the ideal corrosion protection material in a wide variety of industries. Halar® ECTFE has a unique combination of properties that delivers long-lasting performance and includes excellent chemical resistance, outstanding permeation resistance, exceptional surface properties, good adhesion and high purity.

### Waterborne Coating for Corrosion Protection

As a complement to this powder system, Solvay, world leader in high performing polymers, has developed an innovative waterborne Halar® ECTFE coating system.

Composed of a high adhesion liquid primer and a liquid topcoat, the system can be applied using a conventional liquid spray application.

The developed coating system combines the well-known superior performance properties of Halar® ECTFE, with a high level of adhesion to various substrates and high permeation resistance.

Halar® Liquid Coating System exhibits the same performance as the very well known and appreciated Halar® 6014 powder coating system.

### Halar® ECTFE typical properties

Properties	Value
Melting point	220–245 °C
Maximum continuous service temperature (according to UL)	150 °C
Density	1.68 g/L
Broad chemical resistance	pH 1–14

Halar® Liquid Coating System is not a replacement for powder coatings, but offers advantages with respect to the Halar® ECTFE powder coating system:

- An ambient temperature spray extends Halar® ECTFE coatings into new areas of the anticorrosion market not currently covered
- Build coating thickness on parts with low heat capacity
- More precise spray control and better leveling → better coverage with complicated parts and tighter thickness tolerances
- No Faraday cage effect → ability to coat objects with hollows, cavities, recessed areas
- Reduced need for masking → no overspray; will stick irreversibly to areas that must remain uncoated
- Smooth coating at low thickness
- Potential for liquid dip coating

The coating shows very good surface finish.



## Well Designed for Complex Parts and Inaccessible Surfaces

The new Waterborne Halar® ECTFE coating system has been developed to open the range of applications for corrosion protection of:

- Complex parts
- ID pipe coating – long pipes (up to 12 m) – good alternative to CRA pipes and PTFE sleeved pipes<sup>1</sup>
- Internal tank and container coating

### Chemical Resistance

Halar® ECTFE demonstrates excellent overall chemical resistance thanks to the fact that:

- It is virtually unaffected by most harsh chemicals commonly encountered in the industry
- It is a hydrophobic material with exceptional resistance to strong acids and bases (pH 1 – 14)
- It is not dissolved by any known solvent up to 150°C

<sup>1</sup> Most stainless steel grades will be subject to attack, because their chromium content is not sufficient in forming a protective passive layer. Duplex & SuperDuplex are known to be limited by 30% H<sub>2</sub>SO<sub>4</sub> at 85°C.

### Halar® ECTFE properties variation after 30 days continuous exposure

Chemical	Conc. [% by weight]	Test Temp. [°C]	Weight	Mechanical Properties
H <sub>2</sub> SO <sub>4</sub>	98	121	< 1 %	Insignificant
HCl	37	121	< 1 %	Insignificant
HF	50	121	< 1 %	Insignificant
HNO <sub>3</sub>	50	50	< 1 %	Insignificant
H <sub>2</sub> O <sub>2</sub>	30	88	< 1 %	Insignificant
Chlorine water	Saturated solution	40	< 1 %	Insignificant
NaClO	15	100	< 1 %	Insignificant
NaOH	30	121	< 1 %	Insignificant
TMAH	25	100	< 1 %	Insignificant
Methanol	100	65	< 1 %	Insignificant

Data obtained at atmospheric pressure by immersion of compression molded specimens according to ASTM D543

## The Coating Systems

The new Waterborne Halar® ECTFE coating system offers the possibility to work in primer and top coat but also in primerless.

All grades are applied by standard liquid spray equipment and shows:

- Easy and fast application
- Seamless protection reducing risk of failures
- Uniform coating thickness
- Flexibility of final thickness depending on service conditions
- Possibility of coating interior and exterior surfaces
- ID pipe coating

### Characteristics

### Typical Value

Adhesion (500 µm-thick coating)	20 N/mm (film rupture)
Resistance to H <sub>2</sub> SO <sub>4</sub> at 120°C (500 µm-thick coating on carbon steel)	Adhesion maintained
Resistance to V <sub>2</sub> (SO <sub>4</sub> ) <sub>3</sub> & H <sub>2</sub> SO <sub>4</sub> at 40°C (500 µm-thick coating on carbon steel)	Adhesion maintained
Resistance to wet abrasive wear as per ASTM D2486 and ASTM D3450	No significant thickness reduction



Photo courtesy of Hüni GmbH + Co. KG



## Specialty Polymers

### Worldwide Headquarters

**SpecialtyPolymers.EMEA@solvay.com**

Viale Lombardia, 20  
20021 Bollate (MI), Italy

### Americas Headquarters

**SpecialtyPolymers.Americas@solvay.com**

4500 McGinnis Ferry Road  
Alpharetta, GA 30005, USA

### Asia Headquarters

**SpecialtyPolymers.Asia@solvay.com**

No.3966 Jindu Road  
Shanghai, China 201108

[www.solvay.com](http://www.solvay.com)

Safety Data Sheets (SDS) are available by emailing us or contacting your sales representative. Always consult the appropriate SDS before using any of our products.

Neither Solvay Specialty Polymers nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Solvay's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Solvay's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right.

All trademarks and registered trademarks are property of the companies that comprise the Solvay Group or their respective owners.  
© 2019, Solvay Specialty Polymers. All rights reserved. D 10/2018 | R 11/2019 | Version 1.1 Brochure design by ahlersheinel.com